

Chemron



DISLUDGE

\$32.00 – \$252.00

Concentrated degreaser additive, contains no caustics, acids or creosote materials.

Not classed as flammable as flash point is above 65°C.

Raises the flashpoint of most solvents; improved safety with hot machinery.




Makes solvents emulsify in water; improved rinsing. Increases solvent penetration: better cleansing and reduced residue.

- AQIS-approved Category 3 general cleaner type C

SKU: DIS

Chemron

VARIATIONS

Image	SKU	Price	Container Size
	DIS-XU-g-100-DM-001-LTM	\$32.00 ex GST (\$35.20 inc GST)	1LT
	DIS-XU-g-100-DM-005-LTM	\$77.00 ex GST (\$84.70 inc GST)	5LT
	DIS-XU-g-100-DM-020-LTM	\$252.00 ex GST (\$277.20 inc GST)	20LT

PRODUCT DESCRIPTION

Dislodge is a safe, high flashpoint, solvent-based degreaser that can be rinsed off with water.

This product is a concentrated degreaser additive with a high flashpoint of more than 65°C. When added to any hydrocarbon solvent, such as kerosene, it will significantly raise their flashpoint. It also enables solvent-based degreasing agents to emulsify in water which improving rinsing leaving surfaces free of oily residues.

When added to other solvents, it forms an economical solution for all degreasing applications.

With its high flash point, Dislodge is a safer choice when degreasing hot machinery.

Product Features:

- No caustic or acidic component.
- Safe on skin and low in odour.
- Deepens the penetration of solvents, resulting in a more thorough clean.
- AQIS-approved Category 3 general cleaner type C.

Ideal for:

- Removing pre-delivery wax.
- Removing of Protecta.
- Parts washing.
- Cleaning engine bays.
- Cleaning workshop floors.

Dislodge is a highly effective replacement for High Solve.

If you have any questions about using Dislodge as a replacement for High Solve please call us or fill in the form below.

DIRECTIONS FOR USE

Dilution:

- Motors, running gear and the like: With heavy grease and oil build-up: 1 part to 3 parts hydrocarbon solvent.
- With low grease and oil build-up or for soaking parts: 1 part to 10 parts hydrocarbon solvent.
- Removing grease and oil for concrete floors and the like: 1 part to 3 parts hydrocarbon solvent.
- Removing pre-delivery wax: 1 part to 20 parts hydrocarbon solvent.

Cleaning motors, running gear, concrete floors and the like:

1. Spray onto the surface to be cleaned.
2. Allow to dwell for five minutes.
3. Agitate with a brush or broom if required.
4. Thoroughly rinse the area with water. Preferably use a pressure washer.

Removing pre-delivery wax:

1. Apply with a cloth or spray and wipe.
2. Rinse with a pressure washer.

Note: Before using with painted surfaces, we recommend testing in an inconspicuous area first.

DOWNLOADS

- [DIS – Compliance Label](#)

Chemron

YOU MAY ALSO LIKE...



UBC



Specialised Acid Wash



Protecta



Farm Mate