

Chemron

VARIATIONS

Image	SKU	Price	Container Size
	SRF-RC-0-012-LT-005-LTP	\$60.50 \$60.50 (inc GST)	5LT
	SRF-RC-0-012-LT-015-LTP	\$86.90 \$86.90 (inc GST)	15LT

Chemron

PRODUCT DESCRIPTION

Slip Release Foam is a hot-mix asphalt release agent for road sealing equipment. It helps to prevent asphalt from 'sticking' to the equipment and interrupting a smooth discharge and delivery of asphalt.

It has been developed as a replacement for hydrocarbon solvent-based products. Slip Release Foam is biodegradable, non-toxic, phosphate-free and pH neutral. It is both environmentally and user-friendly.

Chemron

DIRECTIONS FOR USE

Roller release agent Dilution: 1 Litre to 1500 Litre of water.

1. Half fill the water tank of the roller with water.
2. Add the required measure of product.
3. Fill the tank slowly and from a bottom feed to avoid excess foaming.

Hot Mix Tipper release agent Dilution: 1 part to between 600 to 1200 parts water depending on local water quality.

1. Apply to hot mix tipper with a foaming gun or industrial sprayer.

Water Tanker Dilution: 1 part to 1200 parts of water.

1. Partially fill the tanker with water.
2. Add the required measure of product.
3. Fill the tank slowly and from a bottom feed to avoid excess foaming.

DOWNLOADS

- [SRF – Compliance Label](#)

Chemron

YOU MAY ALSO LIKE...



Bituclean



Lafferty Foaming Gun



U-Beaut Safety Degreaser



Specialised Acid Wash