

# Chemron



## MASONRY SEALER - YELLOW

**\$275.00 ex GST (\$302.50 inc GST )**

Sealing compound to seal and protect any masonry surface. Penetrates surfaces and seals out grease, oil and battery acid.

Masonry Sealer Yellow is a 'safety yellow' coloured, solvent-based topical masonry sealer formulation designed to be used for safety markings.

Recommended for workshop floors, tiled bathroom and shower block floors (including urinal steps), car parks, food processing areas.

---

**SKU:** MSY-YU-3-100-KB-020-LTM

## PRODUCT DESCRIPTION

Masonry Sealer Yellow is a 'safety yellow' coloured, solvent-based topical masonry sealer formulation designed to be used for safety markings. Its sealing properties also protect masonry surfaces from organic and inorganic contaminants like grease, oil, fat and most chemicals. It is a hard-wearing, non-fading coating that creates a lasting bond with the substrate.

### Product Features:

- Factories
- Masonry and concrete sealer for durable protection
- Aesthetic sandstone sealer
- Prevents absorption of unwanted substances - eliminating odours and unsightly staining
- Suitable for use on vertical surfaces
- Leaves an attractive semi-gloss sheen
- Suitable for use in AQIS-inspected meat and food processing plants

### Ideal for:

- Factories
- Service stations
- Concrete roof tiles
- Shower block areas, including urinal steps
- Meat, fish and other food processing areas

We stock Masonry Sealer - Clear, a tintable topical coating for hard-working floors.

# Chemron

## DIRECTIONS FOR USE

**Coverage:** About 6 square metres per litre.

**Dilution:** First coat for dense surfaces: 1 part to 3 parts Xylene.

1. Remove any loose contamination, dust etc.
2. Ensure surface is silicone-free and oil-free.
3. Ensure the surface is completely dry before application.
4. Apply with a brush or low-pressure sprayer, ensuring even coverage.
5. Allow 20 to 30 minutes between coats.
6. Apply 2 or 3 coats if a light lustre is desirable.

**Note:**

- One good even coat is sufficient to seal.
- Ideal ambient temperatures for application are 10°C to 30°C.
- Avoid applying in windy conditions.
- Do not apply if rain is likely within 12 hours.
- To deepen the penetration of Masonry Sealer we recommend that surfaces are first treated with Xylene.

## DOWNLOADS

- [MSY – Compliance Label](#)

# Chemron

## YOU MAY ALSO LIKE...



**Aqua Repello**



**Xylene**



**Shield It**



**Masonry Sealer - Clear**