Sledge

Low Foaming Caustic Cleaner

Sledge provides effective removal of fats, proteins and burnt-on soils in the dairy and food processing industry. It is a low-foaming high-caustic solution that should be automatically dispensed into food plant CIP systems via conductivity or volumetric control. Low-foam surfactants and sequestrants ensure an efficient clean and residue-free rinsing.

A heavy duty caustic with low foam surfactants provides excellent fat and protein removal and quicker rinsing.

May also be used on floors, walls and airborne. Used widely in food and beverage processing and production, breweries and wineries.

Applications:

- Cleaning smokehouse
- Dairy, breweries, winemaking equipment and food processing plants
- Stainless steel cleaning vats, tanks, silos
- Heat-exchange equipment including pasteurisers and evaporators

Directions for Use:

Dilution:

Use at concentrations of 0.5% to 3%, depending on the level of soiling, the process run time and temperatures.

- For normal dairy and food soils, circulate for 15 to 30 minutes at 60°C to 70°C.
- For heat-treated food soils, circulate for 30 to 60 minutes at 5°C above standard processing temperatures.

Attention: Brewery Operators

We have developed a detailed, step-by-step cleaning and sanitising system which includes an illustrated manual, wall-mountable diagrams and material storage safety signs.

This system was developed in conjunction with two brewery system consulting firms, a supplier of CIP cleaning equipment and several brewers from large and smaller breweries.

If you would like us to send you a kit please contact us via the form below, or by calling us on 1800 812 309.

Features:

- Caustic Liquid & Highly Chelated
- Concentrated & Easily Dispensed
- SLEDGE is made in accordance with HACCP and GMP guidelines
- Helps remove mineral scale along with fat and protein.
- Provides a high quality economical result.
- SLEDGE is suitable for use in AQIS inspected meat and food processing plants
- Peroxyacetic Acid
- No Surfactants.

Pack sizes:

15L